

## CONFIGURABLE HOT RUNNERS, DELIVERING PERFORMANCE AND VALUE, FAST

The hot runner system that can be combined with a wide range of popular 1-8 drop manifold configurations. Allows simple projects to get off the ground faster and more economically. Inject Velocity into your next project and bring your business up to speed.

### KEY FEATURES

#### CONFIGURABLE

- One of the most configurable standardized systems in its class.
- Broad shot range.
- Available as a hot runner system only.

#### HIGH PERFORMANCE


- Excellent thermal profile.
- Optimized melt channels specific to each application.
- Consistent high quality molded parts.

#### FAST DELIVERY

- Drawings available within 24 hours.
- Shortened system delivery lead times.


#### SUPERIOR VALUE

- Performance and reliability at an economical price.



# WIDE RANGE OF CONFIGURABLE OPTIONS

## MANIFOLD OPTIONS



## NOZZLE OPTIONS

NOZZLE RANGE		FEMTO	PICO	CENTI	DECI	HECTO
Shot size* (g)		5 - 10	10 - 20	15 - 50	50 - 500	500 - 3,500
Runner Ø	Non-Valved (mm)	5	5	6	8	12
	Valved (mm)	6	7	8	11	16
Gate sizes (mm)		0.6 - 1.5	0.6 - 2.5	0.6 - 2.5	0.6 - 4.0	1.5 - 5.0
Length range (mm)		37-217	27-157	20-120	28-208	40-240

\*Application dependent.

\*\*Please speak to a Mold-Masters representative for complete warranty details. Some conditions and/or limitations apply. Subject to change without notice.

## AVAILABLE GATING STYLES


### VALVE GATING OPTIONS

- Bi-Metallic C-Valve
- Hot Valve
- Accu-Valve CX
- Accu-Valve MX

### THERMAL GATING OPTIONS

- E-Type Torpedo
- F-Type Torpedo
- Bi-Metallic C-Sprue
- Hot Sprue

### Accu-Valve



## TempMaster™ Me series

For peak performance and superior results, Mold-Masters recommends using TempMaster ME controllers with all Velocity hot runner systems. Unlock your operations full potential with TempMaster.